Clear Vision Bullet Resistant Speak-Thrus

• Disc Overlap Prevents Direct Entry of Projectiles While Allowing Natural Voice Transmission

Virtually Unobstructed Vision

Clear Vision Bullet Resistant Speak-Thrus not only offer two levels of protection, but provide a clear field of vision. The unit is easy to install. Just drill a 6" diameter hole in the bullet resistant window, surrounded by three 5/16" holes spaced at 120° on an 7-1/2" diameter (template included). Then secure the 10" Acrylic or Lexgard Disc using the Stainless Steel Studs provided with the unit. The space between the window and disc allows for clear voice transmission. The 10" disc provides enough overlap to prevent direct entry of projectiles. Stud Sets are also available for customers preferring to fabricate their own discs. Intended for interior use only. Designed for use with 1-1/4" Acrylic or 1-1/4" Lexgard only.

CAT. NO.	DESCRIPTION	PROTECTION
CAD101	10" x 1-1/4" Clear Acrylic Disc with Studs	Level 1
CLD103	10" x 1-1/4" Clear Lexgard Disc with Studs	Level 3

SPECIFICATIONS:

Materials: Clear Acrylic; Clear Lexgard; Stainless Steel

Finish: Studs - Brushed Stainless Steel


Glazing: 1-1/4" Level 1 Acrylic; 1-1/4" Level 3 Lexgard

Bullet Resistance: Level 1 and Level 3

Instructions Included
Glass Fabrication Required







10" Disc

1-1/4" Bullet Resistant Glazing