# Narrow Inset Frame Windows - Aluminum Exterior Glazed Exchange Window

## • Narrow Inset Frame Vision Window Typically Used Above Built In Exchange Drawers in Walk-Up Installations

Narrow Inset Frame Vision Windows are designed for installation in wall openings having a thickness of at least 4". The frame has a uniform design on all four sides, and the selected glazing material will be sealed into the frame for a weathertight installation. Vision Windows are commonly used as sidelites in Multi-Lite Exchange Window units. Also for installation above built in Transaction Drawers or Package Receivers. Installer affixes frame to wall opening, then permanently seals glazing material into frame with included glazing tape. Common sizes are shown below, alternate sizes are available.

### SERIES: N1VEA, N1VEDU, N1VEP

OVERALL SIZE	WALL OPENING SIZE
(W x H)	(W x H)
24" x 36"	24-1/2" x 36-1/4"
30" x 36"	30-1/2" x 36-1/4"
36" x 36"	36-1/2" x 36-1/4"
48" x 36"	48-1/2" x 36-1/4"
60" x 36"	60-1/2" x 36-1/4"
72" x 36"	72-1/2" x 36-1/4"
30" x 42"	30-1/2" x 42-1/4"
36" x 42"	36-1/2" x 42-1/4"
48" x 42"	48-1/2" x 42-1/4"
60" x 42"	60-1/2" x 42-1/4"
72" x 42"	72-1/2" x 42-1/4"



## SPECIFICATIONS:

Materials: Frame - .125" Thick Extruded 6063-T5 Aluminum Alloy; Glazing - 1/4" Glass; 1-5/16" Level 1 Glass; 1-1/4" Level 1 Acrylic; 3/4" Level 1 Lexgard; 1-5/8" Level 2 Glass; 1-7/8" Level 3 Glass; 1-1/4" Level 3 Lexgard Finishes: Frame - Satin Anodized, Duranodic Bronze, RAL Powder Paint Colors or Custom Kynar Paint Colors

1 - 7/16

#### Instructions Included



7/16"

#### PROTECTION LEVEL

