

Accessories and Options for TTU:
Professional Wireless Headset System (Optional)
TTU® -WHS-D: Wireless Headset is designed to work with the TTU-WR Wireless ready unit only.
FEATURES

- Clear 2-way hands-free voice communication.
- Quality engineering and innovative design
- Walk around freely while talking to the customer.
- Self-powered unit with rapid rechargeable battery



ANC 700 Headset (Optional) for use with regular non RF ready units **TTU-NCHS:**

- Superior sound quality
- Noise Cancelation microphone
- Long wearing comfort



7

TTU-3X Series:
Select from following available Models:
TTU-3X 6" Continuous power unit complete with removable XLR mic.
TTU-302WX: One outside unit communicates with two inside units. It is a special design for calling the back office during off business hours.
TTU-3CX is a TTU-3X basic without gooseneck microphone for using headset only.



11

TTU-WHS (Optional)

- Mobile: DECT 6.0 technology hand-free mobile design with range of up to 300 feet from base unit
- Extended Use: Ten hours continuous talk time on rechargeable battery.



Microphone Grill Windshield Sponge:

Specification:

- Material: Foam ,Color: Black
- I D: Approx. 12mm Size: Approx. 65x10mm (L*W)
- High elasticity, durable and soft, Replacement for your worn-out or lost headset microphone pads


Package include:

- 5 x Microphone Covers



8

Handset with Hook-switch (Optional):
Amplified handset with volume control Heavy duty handset with 29" or 48" armored cord Stainless steel plate with chrome hook
Switch Automatic disconnect the speaker and microphone to keep the conversation privacy.



Paging Button (Optional) & speakers for paging
A paging push button switch can be added to TTU-3X for paging over a ceiling speaker. There are 2 types of speaker to meet your application requirement.

- APF-15 High efficiency ceiling or wall mounted horn speaker for direct connect with TTU3XSD for 1 to 2 speaker application.
- SD-72WV Indoor Ceiling Speaker with 25V/70V transformer for uses with UA 35T II Amplifier (Option). It is good for more than 2 speaker application.

12

Introducing the Norcon TTU® -1X NC:
When using a Talk-thru unit in a noisy area such as heavy traffic street, a crowded movie theater hall way or a gas station, the noise makes the conversation difficult. A powerful DSP chip inside the Norcon noise cancelation unit samples an ambient noise environment and attenuate the noise around the desired speech signals. As a result, continuous and repetitive noise is removed; a clear conversation can be had, even with a passing truck in the background. To take the advantage of this new technology, the existing unit can be sent to us for upgrade.



Introducing the Norcon TTU-1X Series:
There are times, when the isolation barrier has a 3" to 4" hole on it, the Norcon TTU-1X is special design for it.
The TTU-1X is a 5" in diameter round unit. The front face and the housing are easily mounted on opposite sides of the barrier. They allow hand free communication through barriers. It is the most widely used system of its type in the U.S. and the world.
TTU-1X series includes TTU-1AX basic model; the TTU-1ABX UL listed level 3 bullet proof unit; with removable gooseneck microphone unit; TTU-1DX rechargeable battery operated unit and much more. Norcon provides audio/visual, communications, and secure talk-thru solutions for critical applications around the world.
Please visit our web-site at www.norcon.org for the entire series of Norcon's high quality product. We are sure you will find one to meet your needs. Special requirements and custom-design projects are welcome.

9

TROUBLESHOOTING:
You may occasionally encounter a problem with your TTU system. If this happens, refer to the following list. If additional help is needed, please contact us.

- No sound at all

Is the power supply properly plugged into a working outlet?
If the power supply has been plugged into a working outlet for a while, the power supply should be warm, if it not; the power supply may be defective.

- Howling (Feedback)

Is the TALK or LISTEN volume turned too high?
Set the volume control to a proper level. In most cases, both TALK and LISTEN should be set to the position of around 11 to 12 o'clock.

- Conversation cutting-off and breaking-up.

Is the TALK volume setting too high?
Turn down TALK volume to a proper level.

- Is the attendant too far from the gooseneck microphone?

The ideal distance is 3" to 4" from the gooseneck microphone.

13

TTU®-1X Series:

Select from available models with detachable XLR mic.

- TTU® -1AX continuous power unit. Housing 5" Dia x 2 ½" depth.
- TTU® -1AWX Wireless ready.
- TTU®-1ABX same as TTU®-1AX, but with bullet-resistant option (UL Level 3).
- TTU®-1ACX same as TTU®-1AX without gooseneck microphone for headset use only.
- TTU®-1DX Battery operated unit. Complete with rechargeable batteries and charger. Housing 5" Dia x 3 ½" depth.
- TTU®-1DBX same as TTU®-1DX, but with bullet-resistant option (UL Level 3).

Talk-Thru systems are shipped complete with cables, instructions, and power supply.

10

Service Policy

TALK-THRU SYSTEM WARRANTY REPAIRS

Norcon Communications Inc. warrants the products Manufactured by Norcon to be free from defects in material and workmanship for a period of one year from the date of shipment from the factory provided:

1)The product has not been abused, misused or improperly maintained, repaired and /or modified during such period, and

2)Such defect is not a result of voltage surges/ burnouts, lightning, water damage / flooding, fire, explosion, earthquakes, tornadoes, acts of aggressions / war or similar phenomenon; and

3) The product has been properly installed according to the appropriate Norcon Installation Guide.

Both incoming and outgoing freight charges are at customer's expenses. Domestic repair will be returned to customer by UPS Ground. International repair will be returned to customer using normal shipping arrangements. Any other shipping instructions must be made in writing and will be at the customer's expense

14